



INTRATEC
100% SHOPPING

**Datasheet
Main switch
Art. No. MKDGH4-01**

Intratec Warenhandels GmbH

Gruetzmuehlenweg 46
22339 Hamburg
Germany

FON: +49 40 538092 888

FAX: +49 40 538092 930

MAIL: info@intratec-hh.de

WEB: www.intratec-shop.de



Electrical specifications

Service voltage: 400V AC

Protection class: IP65

Protected against: Water jets and splashes from all directions, high humidity and water vapour

Areas of application: Outdoors (e.g. garden) and damp rooms such as cellars, garages or bathrooms, water-exposed areas in industry that are frequently cleaned with high-pressure cleaning, for example

Material of housing: acrylic ester styrene acrylonitrile (ASA)

Enclosure colour: Grey RAL 7035

Material door: PC polycarbonate

Door colour: Transparent

Glow wire test: 650°C

Temperature resistance: -25°C to +60°C (thus always reliable even in cold stores, for outdoor use in winter and at high temperatures, such as in direct sunlight)

Halogen-free, RoHS-compliant, CE, UV stable

With built-in DIN rail for all standardised circuit breakers / RCDs according to DIN 43880

Finger-safe N/PE terminal strip

Mounting material

Installation instructions

Dimensions:

A: 201mm

B: 128mm

C: 120mm

E: 78mm

F: 111mm

