



INTRATEC
100% SHOPPING

**Datasheet
Main switch
Art. No. MKHT2X2-02**

Intratec Warenhandels GmbH

Gruetzmuehlenweg 46
22339 Hamburg
Germany

FON: +49 40 538092 888

FAX: +49 40 538092 930

MAIL: info@intratec-hh.de

WEB: www.intratec-shop.de



Electrical Specifications

For auxiliary power applications

consisting of 4 buttons:

1L: Emergency stop mushroom button (2NC simultaneous)

1R: On button (1NO)

2L/2R: 2-stage lifting trolley (2NO each stepped)

incl. hook/kink protection hose on top

Marking: CE

Test voltage: 2500V ~

Max. Operating voltage: 400V ~

Temperature resistance operation: -25°C - +70°C

Protection class: Class II

Protection class: IP 65

Contacts:

Marking: CE / harm. Regulations: EN60947-5-1

Rated voltage: 660V ~

therm. Rated current: 10A

Lifetime: 3 million operations

Max. Cable cross-section: 2x1,5mm² or 1x2,5mm²

Connections: finger-safe screw connection

Limit value:

AC15	Ve(V)	24	48	120	240	400
	Ie (A)	10	10	6	3	1,9
DC13	Ve(V)	24	48	125	250	
	Ie (A)	5	5	2,2	1,1	

Dimensions:

A= 165mm

H= 75mm

